

QUIK-Stick HT PRO+

High-temperature (smooth poly surface)

Uses & Description

QUIK-Stick HT PRO+ is an SBS modified self-adhesive membrane reinforced with a superior surface polyester mat for high strength, durability and ease of application. Its non-abrasive polyester surface is excellent for use on decks 2:12 and greater under Metal and Tile roof applications.

Benefits

- Offers a skid resistant, polyester surface.
- Silicone-treated, split-back, release film allows for easy installation and handling
- Softening point is a minimum of 250°F
- May be installed directly to concrete, plywood, wood composition board and gypsum
- Self seals around nails
- May be used in new construction or re-roofing
- Offers greater tear resistance than traditional felt underlayment
- Provides protection for critical areas such as rakes, eaves, valleys, flashings, hips, ridges, dormers and skylights
- Provides excellent low temperature flexibility
- May be left exposed up to 180 days prior to application of finished roof
- Florida Approval (FL #30520)
- Miami-Dade Approval



Specifications

ASTM	D 1970
Thickness	60 mils
Maximum Load, nominal (lbf/inch-width)	MD=60, CD=50
Elongation at Break (%)	50
Adhesion to Plywood @ 77 °F (lbf/inch-width)	50
Thermal Stability (max)	0.05
Flexibility Temperature, @ -20 °F	pass
Sealability around nail	pass
Moisture Vapor Permeance (US Perms)	< 0.01
Water Proof Integrity after Low Temp. Flex	pass
Waterproof Integrity of lap seam	Pass
Slip Resistance	pass
Rolls per Pallet (label)	25
Roll Weight, nominal (lbs)	70+/-2
Available roll dimensions	39 1/3" x 61.2'