

QUIK-STICK IW Ice & Water

QUIK-STICK Ice and Water is an SBS modified self-adhering membrane reinforced with non-woven fiberglass mat for extra strength and durability. QUIK-STICK IW is a highly versatile underlayment that provides superior waterproof integrity and is an excellent second wall of defense against wind driven rain and seepage due to ice damming.

For use on decks 2:12 and greater.

Benefits:

- Offers a skid resistant, granular surface
- Allows for easy installation and handling as a result of silicone treated split back release film
- Provides high temperature stability
- May be installed directly to concrete, plywood, wood composition board and gypsum
- Self seals around nails
- May be used in new construction or re-roofing
- Up to 60 day exposure prior to application of finished roof
- Offer greater tear resistance than traditional felt underlayment
- Provides protection for critical areas such as rakes, eaves, valleys, flashings, hips, ridges, dormers, and skylights
- Provides excellent low temperature flexibility
- Florida Approval (FL # 17401)
- Miami-Dade Approval

Specifications:

Reference ASTM	1970
Thickness, min	50mils
Maximum Load, min	35 MD 35 CD
Elongation at Break, min	30%
Adhesion to Plywood @ 77°F min	20.0lbf/ft
Thermal Stability, max	0.05
Flexibility Temp., @ -20°F min	pass
Sealability around nail	pass
Waterproof Integrity after low temp. Flex	pass
Waterproof Integrity of lap Seam	pass
Slip Resistance	pass



Roll Breakdown

Roll Dimensions 2 SQ	36" x 65'
Roll Dimension 1 SQ	36" x 33.4'
Square Feet 2 SQ	195
Square Feet 1 SQ	100
Rolls per pallet 2 SQ	30
Rolls per pallet 1 SQ	49
Roll Weight 2 SQ	60lbs ± 2lbs
Roll Weight 1 SQ	33lbs ± 2lbs
Roll Diameter 2 SQ	8.75"
Roll Diameter 1 SQ	6.5"