

QUIK-STICK SAS

Self - Adhered Synthetic

MSA QUIK-STICK SAS is a self-adhered high temperature underlayment designed for steep slope roofing applications. Manufactured as a secondary water barrier, SAS can be used as an underlayment in a variety of roofing systems such as under asphalt shingles, metal, tile, etc.

Features:

- 180 Day UV Resistance
- Polypropylene Non-Woven Surface
- Easy to use Split -Release liner
- Slip Resistant Walking Surface

Codes & Compliances:

- Meets ASTM D1970
- FBC Approved (FL# 47221)

Roll Specifications:

- 36" x 66.7 liner feet
- 41 lbs per roll
- 2 SQ Roll
- 25 rolls per pallet



Technical Data:

PROPERTY	SPECIFICATION	TEST METHOD
Nominal Thickness	41 mil	ASTM D5147
Nail Sealability	PASS	ASTM D1970
Moisture Vapor Perm.	<0.1 perms	ASTM E96
Tear Resistance	>20 MD >20 CD	ASTM D1970
Max Load	108 MD 88 CD	ASTM D1970
Elongation	142 MD 175 CD	ASTM D1970
Thermal Stability	250° F (121° C)	ASTM D1970
Adhesion to Plywood	PASS	ASTM D1970