

HT PRO +

High-Temperature Smooth Poly Surface

QUIK-Stick HT Pro + is a high strength SBS-modified self-adhesive membrane surfaced with reinforced polyester fabric. This polyester surface provides improved traction while working on the roof. It's designed for use under Tile Roofing applications and can also be installed as part of a 2-Ply system with our HT Pro Underlayment.

Benefits:

- Offers a skid resistant, polyester surface
- Silicone-treated, split-back, release film allows for easy installation and handling.
- Softening point is a minimum of 250°F
- May be installed directly to concrete, plywood, wood composition board and gypsum
- Self sealing around nails
- May be used in new construction or re-roofing
- Offers greater tear resistance than traditional felt underlayment
- Provides protection for critical areas such as rakes, eaves, valleys, flashings, hips, ridges, dormers, and skylights
- Provides excellent low temperature flexibility
- Up to 180 day exposure prior to application of finished roof
- Florida Approval (FL # 30520)
- Miami-Dade County Approved



Specifications:

Reference ASTM	1970
Thickness, min	60 mils
Maximum Load, min	60 MD 50 CD
Elongation at Break, min	50%
Adhesion to Plywood @ 77°F min	50.0lbs/ft
Thermal Stability, max	0.05
Flexibility Temp., @ -20°F min	pass
Sealability around nail	pass
Moisture Vapor Permeance (US Perms)	<0.01
Waterproof Integrity after low temp. Flex	pass
Waterproof Integrity of lap Seam	pass
Slip Resistance	pass

Roll Breakdown

Roll Dimensions 2 SQ	39.33" x 61.2'
Square Feet 2 SQ	216
Rolls per pallet 2 SQ	25
Roll Weight 2 SQ	70lbs ± 2lbs