



QUIK-STICK FS (FILM SURFACE)

High-temperature (textured film surface)

USES & DESCRIPTION

QUIK-Stick FS is an SBS modified self-adhesive membrane reinforced with non-woven fiberglass mat for superior strength, durability and ease of application. It's textured film surface provides improved traction while applying the product. This material is suitable for shingles and metal applications. For use on decks 2:12 and greater.

BENEFITS

- Offers a skid resistant, plastic film surface.
- Silicone-treated, split-back, release film allows for easy installation and handling.
- SBS modified asphalt softening point (ASTM D 36) is a minimum of 250°F.
- May be installed directly to concrete, plywood, wood composition board and gypsum.
- Self seals around nails.
- May be used in new construction or re-roofing.
- Offers greater tear resistance than traditional organic felt underlayment.
- Provides protection for critical areas such as rakes, eaves, valleys, flashings, hips, ridges, dormers and skylights.
- Provides excellent low temperature flexibility.
- FL # 17401

SPECIFICATIONS

ASTM D	1970
Thickness, min	45 mils
Maximum Load, nominal (lbf/inch-width), min	MD=25, CD=25
Elongation at Break (%)	10
Adhesion to Plywood @ 77 °F (lbf/inch-width)	15
Thermal Stability (max)	0.05
Flexibility Temperature, @ -20 °F	pass
Sealability around nail	pass
Moisture Vapor Permeance (US Perms)	< 0.03
Waterproof Integrity after Low Temp. Flex	pass
Waterproof Integrity of lap seam	pass
Slip Resistance	pass
Rolls per Pallet	30
Roll Weight, nominal (lbs)	48+/-2
Available roll dimensions	36"x66.8' (200sqft)

