

QUIK-Stick HT Pro

High-temperature (textured film surface)

Uses & Description

QUIK-Stick HT Pro is an SBS modified self-adhesive membrane reinforced with non-woven fiberglass mat for superior strength, durability and ease of application. It's textured film surface provides improved traction while working on the roof and is designed for use in metal roof systems application.

For use on decks 2:12 and greater.

Benefits

- Offers a skid resistant, plastic film surface.
- Silicone-treated, split-back, release film allows for easy installation and handling
- SBS modified asphalt softening point (ASTM D 36) is a minimum of 250°F
- May be installed directly to concrete, plywood, wood composition board and gypsum
- Self seals around nails
- May be used in new construction or re-roofing
- Offers greater tear resistance than traditional organic felt underlayment
- Provides protection for critical areas such as rakes, eaves, valleys, flashings, hips, ridges, dormers and skylights
- Provides excellent low temperature flexibility
- Miami-Dade County Approved
- May be left exposed up to 90 days prior to application of finished roof
- FL #17401

Specifications

ASTM	D 1970
Thickness	60 mils
Maximum Load, nominal (lbf/inch-width)	MD=60, CD=50
Elongation at Break (%)	30
Adhesion to Plywood @ 77 °F (lbf/inch-width)	30
Thermal Stability (max)	0.05
Flexibility Temperature, @ -20 °F	pass
Sealability around nail	pass
Moisture Vapor Permeance (US Perms)	< 0.03
Water Proof Integrity after Low Temp. Flex	pass
Waterproof Integrity of lap seam	Pass
Slip Resistance	pass
Rolls per Pallet (label)	25
Roll Weight, nominal (lbs)	70+/-2
Available roll dimensions	36"x66.8' (200sqft)

