

## APC PRECISION STAIN

Concentrate UV Stable for Interior and Exterior Use

Let Down With Acetone Only


Find us on  
Facebook.



**APC PRECISION STAIN** - Precision stains are ideal for decorative concrete applications including flatwork, countertops, stamped and overlays. Attractively priced, **APC Precision Stains** are suited for residential interior and exterior spaces and commercial applications including restaurants, retail, hospitality, shopping malls, theaters, theme parks, building entries, patios and sidewalks. **APC Precision Stain** transforms plain concrete into attractive decorative concrete without the harsh chemicals, the tedious process, and expense of acid staining. **APC Precision Stain** is a concentrated stain that dilutes in acetone. Beginning with a properly prepared surface, these stains can be applied and sealed in as little as one day, minimizing down-time. The semitransparent properties allow the variations in the substrate to enhance the final look. Choose from 10 stock colors. The color palette becomes much greater by combining stock colors to create your own unique effect. Make sure to finish the surface with **APC Precision Seal** products to protect and enhance the lasting beauty of your design.



Red Rock




Painted Desert




Canyon




Tumbleweed



Frost



Riviera




Cactus



Amarillo




Smoke



Saltillo



Hickory



Java



Midnight

\*Actual colors vary on each piece of concrete\*

# APC PRECISION STAIN



## Materials and Tools Required

Acetone resistant pump up sprayer with conical tip  
Absorbent cloth or small container to catch drips  
Painter's masking tape and plastic sheeting  
**APC Precision Clean & Etch, APC Precision Neutralizer Degreaser and APC Precision Stain**  
Synthetic bristle brush (optional)  
Acetone for cleaning equipment

## Surface Preparation

The surface should be free of dirt and oil. Substrate should be 4 weeks old. Clean with **APC Precision Clean & Etch** to profile and clean the concrete surface. For extremely dirty surfaces, **APC Precision Neutralizer Degreaser** is recommended. Rinse with clean water. If possible power wash the surface at 3000 psi. Allow the surface to dry 24 hours before applying the stain. All walls, furniture, columns or other items/areas that you do not want to color should be masked using painter's tape and plastic sheeting. This will protect the items from overspray. Always do a test spot in an inconspicuous area before proceeding.

## Stain Preparation

**APC Precision Stain** concentrate should be added to one gallon of acetone in sprayer. Use acetone to rinse color concentrate from bottle. Mix the two ingredients thoroughly.

## Application

Apply with an acetone-resistant pump up sprayer using a conical, fine spray tip. Small areas can be brushed using circular motions to avoid brush strokes. Take care to maintain a wet edge to avoid lines, and avoid puddling **APC Precision Stain**. Avoid drips. Prior to application, tape a piece of cloth or a small container to the sprayer body to catch drips while not spraying the material. Place the tip of the spray wand on the cloth or into the small container immediately after releasing the spray handle. Apply the stain uniformly to obtain a more uniform final appearance. Apply in a random, circular motion with some overlapping to generate a more mottled look and more closely resemble acid stain. Colors may be blended to produce a large palette or applied over a base color for a unique look. Depending on the depth of color that is desired, coverage rates will vary.

## Sealing

Seal as soon as concrete is dry to touch. Spray apply the first coat of sealer to lock in color. **APC Precision Stain** can be sealed with most any sealer, **APC Precision Seal 19** is recommended for exterior applications. For interior applications, **APC Precision Poly**, a 2-component system is very durable. **APC Precision Clear Seal WB** is a low odor water based alternative if floor is not too tight. Clean sealed floors with water only and use **APC Precision Wax Polish** on interior floors for added protection.

## Coverage Rates

Approximately 200 square feet per gallon for smooth concrete, depending on depth of color desired. More material will be required for more porous surfaces or deeper coloration.

## Technical Data

VOC: <350 g/L  
Flash Point: 114

## HMIS/NFPA

Health	1	Flammability	2
Reactivity	0	Protection	B

## Disclaimer

The facts stated and recommended regarding APC products are based on our own research and the research of others, and are believed to be accurate. APC products are sold without WARRANTY, expressed or implied, and on the condition that the purchasers conduct their own tests in order to determine the suitability of such for their particular purpose. The user is solely responsible for the use and information regarding APC products. APC disclaims any liability. APC disclaims any warranty of merchantability or fitness of this product for any particular purpose. The suitability of the product for any use shall be solely up to the user. Manufacturer retains right to legal venue.

Rev. May 2013