

QUIK-Stick IW

Ice & Water

Uses & Description

QUIK-Stick Ice & Water is an SBS modified self-adhering membrane reinforced with non-woven fiberglass mat for extra strength and durability. QUIK-Stick IW is a highly versatile underlayment that provides superior waterproof integrity and is an excellent second wall of defense against wind driven rain and seepage due to ice damming.

For use on decks 2:12 and greater.

Benefits

- Offers a skid resistant, granular surface
- Allows for easy installation and handling as a result of silicone treated split back release film
- Provides high temperature stability
- May be installed directly to concrete, plywood, wood composition board and gypsum
- Self seals around nails
- May be used in new construction or re-roofing
- May be left exposed up to 60 days prior to application of finished roof
- Offers greater tear resistance than traditional felt underlayment
- Provides protection for critical areas such as rakes, eaves, valleys, flashings, hips, ridges, dormers and skylights
- Provides excellent low temperature flexibility
- Florida Approval (FL #17401)
- Miami-Dade Approval

Specifications

Reference ASTM	1970
Thickness, min	50 mils
Maximum Load, min	MD=35 CD=35
Elongation at Break, min	30%
Adhesion to Plywood @ 77 °F min	20.0 lbf/ft
Thermal Stability, max	0.05
Flexibility Temperature, @ -20 °F min	pass
Sealability around nail	pass
Water Proof Integrity after Low Temp. Flex	pass
Waterproof Integrity of lap Seam	pass
Slip Resistance	pass
Rolls per Pallet 2SQ (label/box)	25 / 25
Rolls per Pallet 1SQ (box only)	30
Roll Weight	1sq - 33lbs+/-2lb 2sq - 68 lbs ± 2lbs
Roll Diameter	1sq - 6.5 in. 2sq - 8.75 in.
Square feet	100/195
Available roll dimensions	36" x 33.4' (100sqft) 36" x 65' (195sqft)

