

QUIK-Stick IWS

Ice & Water Sand

Uses & Description

QUIK-Stick Ice & Water Sand is an SBS modified self-adhering membrane reinforced with non-woven fiberglass mat for extra strength and durability. QUIK-Stick Ice & Water sand is a highly versatile underlayment that provides superior waterproof integrity and is an excellent second wall of defense against wind driven rain and seepage due to ice damming.

For use on decks 2:12 and greater.

Benefits

- Offers a skid resistant, sand surface
- Allows for easy installation and handling as a result of silicone treated split back release film
- Provides high temperature stability
- May be installed directly to concrete, plywood, wood composition board and gypsum
- Self seals around nails
- May be used in new construction or re-roofing
- May be left exposed up to 60 days prior to application of finished roof
- Offers greater tear resistance than traditional felt underlayment
- Provides protection for critical areas such as rakes, eaves, valleys, flashings, hips, ridges, dormers and skylights
- Provides excellent low temperature flexibility
- Florida Approval (FL #17401)
- Miami-Dade Approval

Specifications

Reference ASTM	1970
Thickness, min	50 mils
Maximum Load, min	MD=35 CD=35
Elongation at Break, min	30%
Adhesion to Plywood @ 77 °F min	20.0 lbf/ft
Thermal Stability, max	0.05
Flexibility Temperature, @ -20 °F min	pass
Sealability around nail	pass
Water Proof Integrity after Low Temp. Flex	pass
Waterproof Integrity of lap Seam	pass
Slip Resistance	pass
Rolls per Pallet (label / box)	25 / 25
Rolls per Pallet (box only)	30
Roll Weight	68 lbs ± 2lbs
Roll Diameter	7.5 in.
Square feet	100/195
Available roll dimensions	36" x 33.4' (100sqft) 36" x 65' (195sqft)

